



Carbon, Flexback, Hardedge Bandsaw Blades



Carbon steel is inexpensive & readily available with a variety of tooth configurations & widths.

Features:

Heat treated European steel, High Alloy, Carbon steel. Tooth hardness 64-67 Rc. Back hardness 28-35 Rc.

Advantages:

Fast, clean cuts. Fatigue resistant at high speeds. Multiple widths for contour and straight cuts.

Benefits:



High productivity in wood cutting. Low cost. Excellent wear resistance in wood applications.

Applications:

For hard and soft wood cutting and re-sawing. For plastic, cork, fiberglass, graphite, aluminum, brass, bronze, cast iron, lead, zinc, etc.

To Order:

We will weld your bandsaw blade to ANY length. Specify length x Width x TPI (teeth per inch).



		4s	4, 4s, 6, 6s	3, 3s, 4, 4s, 6	3, 4, 4s, 6, 8,	2, 3, 3s, 4, 6	2, 3, 4, 6	1.14, 1.3	1.14, 1.3	1.14	1.3
TPI Hook											
TPI Raker	14, 18, 24	10, 14, 24	8, 10, 14, 18, 24	8, 10, 14, 18, 24	10, 14, 18, 24W	8, 10, 14, 18	8, 10, 14		1		
Thickness	(.025")	(.025")	(.025")	(.025")	(.025")	(.032")	(.035")	(.035")	(.042")	(.045")	(.035")
Width	1/8"	3/16"	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/4"	1 1/2"	2"
Length	42" - 300"										

SAWING

Bi-Metal Bandsaw Blades European Steel



Features:

Matrix II, Welded Edge Tempered Alloy Backer. Hardness 66-68Rc.

Advantages:

High heat resistance. Shock & wear resistant teeth. Fatigue resistant.

Benefits:


High productivity. Longer life than carbon. Quick tooth penetration.

Applications:

For general purpose cutting of ferrous metal, tool steel, solids, shapes, tubing & structural shapes.

To Order:

We will weld your bandsaw blade to ANY length. Specify length x Width x TPI (teeth per inch)



		4s	4, 4s, 6, 6s	3, 3s, 4, 4s, 6	3, 4, 4s, 6, 8,	2, 3, 3s, 4, 6	2, 3, 4, 6	1.14, 1.3	1.14, 1.3	1.14	1.3
TPI Raker	10, 14	4h, 8, 10, 14	10, 14, 18,	4h, 6h, 10, 14, 18	3h, 10, 14	4h, 6, 10, 14					
TPI Variable	10-14	10-14	10-14, 24W	6-10, 8-12	3-4, 4-6, 5-8	2-3, 3-4, 4-6, 5-8	2-3, 3-4, 4-6				
TPI Variable			Special	10-14, 14-18	6-10, 8-12, 10-14	6-10, 8-12, 10-14	5-8, 6-10, 8-12				
Thickness	(.025")	(.025")	(.020")*	(.025")	(.035")	(.035")	(.042")				
Width	1/4"	3/8"	1/2"	1/2"	3/4"	1"	1 1/4"				
Length	42" - 300"										