



Carbon, Flexback, Hardedge Bandsaw Blades



Carbon steel is inexpensive & readily available with a variety of tooth configurations & widths.

Features:

Heat treated European steel, High Alloy, Carbon steel. Tooth hardness 64-67 Rc. Back hardness 28-35 Rc.

Advantages:

Fast, clean cuts. Fatigue resistant at high speeds. Multiple widths for contour and straight cuts.

Benefits:



High productivity in wood cutting. Low cost. Excellent wear resistance in wood applications.

Applications:

For hard and soft wood cutting and re-sawing. For plastic, cork, fiberglass, graphite, aluminum, brass, bronze, cast iron, lead, zinc, etc.

To Order:

We will weld your bandsaw blade to ANY length. Specify length x Width x TPI (teeth per inch).



	4s	4, 4s, 6, 6s	3, 3s, 4, 4s, 6	3, 4, 4s, 6, 8,	2, 3, 3s, 4, 6	2, 3, 4, 6	1.14, 1.3	1.14, 1.3	1.14	1.3
TPI Hook										
TPI Raker	14,18, 24	10,14, 24	8,10,14,18, 24	8, 10, 14,18, 24	10, 14, 18, 24W	8, 10, 14, 18	8,10,14		1	
Thickness	(.025")	(.025")	(.025")	(.025")	(.025")	(.032")	(.035")	(.035")	(.042")	(.045") (.035")
Width	1/8"	3/16"	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/4"	1 1/2" 2"
Length	42" - 300"									

Bi-Metal Bandsaw Blades European Steel



Features:

Matrix II, Welded Edge Tempered Alloy Backer. Hardness 66-68Rc.

Advantages:

High heat resistance. Shock & wear resistant teeth. Fatigue resistant.

Benefits:



High productivity. Longer life than carbon. Quick tooth penetration.

Applications:

For general purpose cutting of ferrous metal, tool steel, solids, shapes, tubing & structural shapes.

To Order:

We will weld your bandsaw blade to ANY length. Specify length x Width x TPI (teeth per inch)



	10, 14	4h, 8, 10, 14	10, 14, 18,	4h, 6h, 10, 14, 18	3h, 10, 14	4h, 6,10, 14	
TPI Raker							
TPI Variable	10-14	10-14	10-14, 24W	6-10, 8-12	3-4, 4-6, 5-8	2-3, 3-4, 4-6, 5-8	2-3, 3-4, 4-6
TPI Variable			Special	10-14, 14-18	6-10, 8-12,10-14	6-10, 8-12, 10-14	5-8, 6-10, 8-12
Thickness	(.025")	(.025")	(.020")*	(.025")	(.035")	(.035")	(.042")
Width	1/4"	3/8"	1/2"	1/2"	3/4"	1"	1 1/4"
Length	42" - 300"						